

K. Specifications

Performance

pHoenix XL	Conductivity						Temp.	pH
Range	0 μ S/cm to 99 μ S/cm	100 μ S/cm to 1.99 mS/cm	2.0 mS/cm to 19.9 mS/cm	20.0 mS/cm to 79.9 mS/cm	80.0 mS/cm to 119 mS/cm	120 mS/cm to 200 mS/cm	15°C to 90°C	2 to 12 pH Units
Accuracy	+/- 5 μ S/cm	+/- 10 μ S/cm	+/- 0.1 mS/cm	+/- 1 mS/cm	+/- 2 mS/cm	+/- 5 mS/cm	+/- 0.5°C	+/- 0.1 pH Units
Resolution	1 μ S/cm	10 μ S/cm	0.1 mS/cm	1 mS/cm	1 mS/cm	1 mS/cm	0.1°C	0.1 pH Units
Temperature Compensation	15°C to 45°C						N/A	N/A
Units of Measure	μ S*, mS*, ppm (Na ₂ CO ₃)						°C, °F	pH Units

*Unit displays μ S representing μ S/cm and mS representing mS/cm.

Physical

Dimensions: H 11.0" x D 1.625" x W 2.875" (28 cm x 4.1 cm x 7.3 cm)

Weight: 8.8 oz. (249 gm)

Power: Battery

Battery Type: 3.6V Lithium (P/N 210427-001)